

# Vishvakarma



## : FEATURES :

- FULLY INSULATED TANK WITH HIGH PERFORMANCE OIL HEATING
- AIR COOLED DIESEL ENGINE AND POSITIVE DISPLACEMENT GEAR PUMP
- FULLY-CIRCULATING SPRAY BAR
- OPERATOR'S PLATFORM WITH HOOD
- SIMPLE PRESSURE CLEANING SYSTEM PROVIDED
- DIGITAL SPEED INDICATOR
- MOISTURE SEPARATOR FOR CLEAN & DRY AIR

**\* Quality that you can rely upon \***

# Vishvakarma

## BITUMEN SPRAYER - Specification

BITUMEN TANK	
Model	: 4000/6000 VBS
Capacity	: 4000/6000 Liters.
Tank Shape	: Oval
Insulation	: 50 mm thick glass wool
Temperature Gauge	: 0-300 °C
Manhole	: 450 mm Dia.
Mounting	: Tank Mounted on any truck chachis of wheel base 176"/166"
SPRAY BAR	
Length	: 2.5 mtr.
Length with Extension	: 4.00 mtr.
Control of Spray Bar	: Pneumatically Operated
Pre-Heating of Spray Bar	: Fully circulating of pre-heated Bitumen
Bitumen Spraying Pressure	: 0-4 Kg./cm <sup>2</sup>
BITUMEN PUMP	
2" X 2" size positive displacement gear pump with output of 400 Ltrs./Min.	
AIR COMPRESSOR	
Standard make 2 Cyl. air compressor.	
BURNER	
Fuel Consumption	: 20 Ltr./hr.
FUEL TANK	
130 Ltrs. Capacity	
ENGINE	
Standard make air cooled diesel engine.	

Note : Specification are subject to change without notice due to development.

SINCE  
1981



**Vishvakarma** Road Equipment Co (P) Limited.

Near S. D. Chambers, Borsad - 388540. Gujarat (INDIA)

Phone : 02696 - 221317, 221217, 223297 Fax : 222926

E-mail : vreco@vishvakarma.com Website : www.vishvakarma.com